



BACKPACK Instruction

MATERIAL REQUIREMENT:

- 1 Dring (3 cm.)
- 2 x Rectangle ring (2 cm.)
- 1 Turn Lock Closure (2 cm.)
- 12 Grommets or snap ring
- 3 x Buckle (2 cm.)
- Cotton or hemp rope 0.8 - 1.0 cm. diameter, length 22.5 cm/ 9 inch
- 2 mm. round piping cord (82 cm/ 32 1/4 inch)
- Stiffener, foam or other flexible material for the main body back and behind the zipper area (optional)
- Fusible Fleece (optional)
- YKK Zipper No#5: Zipper length approx. 19 cm/ 7 1/2 inch x 2
- Zipper head, zipper pull, zip stopper for No#5 zipper
- Texon or crafts paper use to help straighten the zipper fabric

**Please note: we recommend purchasing zipper by yard or meter then trim it to size

See the YouTube link for the making of this bag: <http://bit.ly/2kkgCXC>

***NOTE: this is an instruction file only. Please refer to the file named "Pattern_.....pdf" to print the pattern pieces




BACKPACK

Instruction

1.



Stitch the strap (D-5) to Mainbody Back (D1)
- see the pattern for start and end position





BACKPACK Instruction

2.




Iron the fusible fleece (D-1 LSF) to the back of the flap lining (D-1 L). Fold the edge of the flap lining in wrapping the fusible fleece



Glue or double sided tape the flap lining (D-1 L) to the flap (D-1)




Stitch around the flap





BACKPACK Instruction

3.




Cut the cotton or hemp rope to 22.5 cm then use masking tape at the end to taper the rope



Glue the rope in the middle of rounded handle (D-3)




Glue D-4 at both ends






BACKPACK Instruction

4.



Fold the rounded handle in position and stitch





BACKPACK Instruction


5.



Cut the capsule holes on the strap holder (D-3).




Glue rounded handle (D-2) to position in the strap holder (D-2) then stitch.






BACKPACK Instruction

6.



- Glue the stiffener (B-2 ST) to the mainbody back (B-2)
- Punch holes through at the top (see pattern for position)






BACKPACK Instruction

7.




Glue the flap (D-1) to the mainbody back (B-2) and stitch







BACKPACK Instruction

8.



- Punch holes on top
- Cut slots for the zipper
- Glue the stiffener (B-1 ST) to the mainbody front (B-1)






BACKPACK Instruction

9.



Measure and cut 2 pieces of YKK Zipper No#5: Zipper length approx. 19 cm or 7 1/2 inch



- Cut texon or crafts paper 19 cm x 0.5 cm
- Glue texon to the edge of the zipper fabric

10.



Insert zip stopper to both ends of the zipper teeth



Bend down the zip stopper to lock in place



BACKPACK Instruction


11.



Glue the zipper to the mainbody front



Use double sided tape or textile glue the pocket lining (B-1 LP)
and stitch the pocket lining to the bottom line of the zipper








BACKPACK

Instruction

12.



Fold over and glue the pocket lining (B-1 LP) to the top line of the zipper fabric



Stitch the pocket lining in place




BACKPACK

Instruction

13.



Glue and stitch mainbody back to main body front overlapping at 1 cm.






BACKPACK Instruction


14.



Glue 2 mm. round piping cord to the middle of the piping leather. Leave 1 cm extra piping cord at the edge




0.4 - 0.5 mm leather thickness recommended




Fold the piping leather

15.



- Glue the piping starting in the middle
- Slit the piping at the corners





BACKPACK Instruction

16.



Glue another piece of the piping leather at the middle point



Cut the excess piping cord at the end and wrap the piping leather overlapping at 1 cm.



Prick holes as close to the piping as possible




BACKPACK Instruction

17.




Skive one side of the bottom stripe front/ back



Stitch the bottom stripe front (A-3) to
bottom stripe back (A-4) in loop



Glue the bottom stripe to the bottom piece





BACKPACK Instruction

18.



Glue 2 cm rectangle ring to the ring holder




Glue the ring holder to the bottom stripe



Stitch



Flip the right side out





BACKPACK Instruction

19.



- Glue and stitch the bottom stripe to the mainbody
- **the mainbody should touch the bottom when glued






BACKPACK Instruction

20.




Insert 2 cm. buckle to D-7



Glue and fold D-7 to lock the buckle in place



Install turn lock closure at the end of the fold





BACKPACK Instruction


21.



Slide the buckle to strap




Install the turn lock closure to the body





BACKPACK Instruction

22.




Use B-3 as template for the stiffener, glue the stiffener to B-2 (L)

**This step is optional (it is to help stiffen the pocket opening area)

**Use texon or crafts paper for stiffener




Slit and punch holes on both ends






BACKPACK Instruction

23.



Slide in B-1 (LP) through the slit of B-2 (L)

24.



Glue B-3 on top

Stitch the bottom 2 lines




BACKPACK Instruction

25.



Fold the pocket downward, glue or double sided tape so the edge is flat



Fold and glue the pocket to the top line of the pocket opening.



Stitch the top and the sides

26.



Stitch the mainbody lining and the bottom together to form a bag



Place the lining inside of the backpack, glue at the top





BACKPACK Instruction

27.



Glue the binding B-4 to the top opening and stitch



Fold the binding in half over the lining



Stitch to secure

*0.5 mm leather thickness recommended

28.



Install grommets or snap rings





BACKPACK Instruction

29.



Fold the stinglet in half and stitch
*0.5 mm leather thickness recommended




Slide the stinglet through the grommets




BACKPACK Instruction

30.




Insert the 2 cm buckle to D-5



Fold and glue to lock the buckle in place



Stitch the sides leaving the ends unstitched



Slide the ends to rectangle ring and stitch to lock





BACKPACK Instruction

31.



Stitch the sides of D-6 leaving the ends unstitched



Slide the end of D-6 to the dring and stitch to lock the position



Measure and punch holes for the buckle

