

First off, thanks for purchasing this pattern!

Instructions:

- *Print this pattern using US Letter or A4 type paper sheets and make sure that you disable the page margins from the printing options before you start.*

- *The parts outlined with a simple line and filled with a gray shade need to be cut out and assembled together after trimming the areas marked with a dashed line and a scissor. Ex:*



- *The dotted lines represent areas where the leather needs to be folded. Not to be confused with the hollow circles which demarcate rivet holes or stitching holes that are to be punched out. Ex:*



- *The puzzle piece that you may encounter is there for making sure you are aligning the right pieces in their proper order.*



- *The outlined circles need to be punched out and the size of the holes will be left out to your preference depending on what type of accesories or tools you have in use (Example: rivets, needles, snap fasteners, stitching punches, hole punches, etc). Ex:*



- *When you're done with cutting and assembling the pattern parts, I advise using paper adhesive tape in order to steady the pattern on top of the leather. After you've made sure everything is in place and not going anywhere you can begin work by firstly punching out the stitching holes and any other marked out holes, then proceed to cutting the outlined shapes, in this precise order. Try leaving the borders last in case you have to work with a more complex model, such that the pattern will stay fixed on top of the leather all throughout the process.*

Let's get to work.

You will need 6-7 oz (2-3 mm) thick leather for this project along with two screw in ball head studs and a D ring that's at most 35mm in total length and 4 mm in thickness. Print the pattern and make sure to measure the small test square that should be 2.54mm (1 inch) in length. Loosely cut around every part and then loosely cut your leather parts using the shapes of the paper parts as reference. You will need to fasten the paper parts that you've cut on top of the leather parts using adhesive paper.

When you're done with the last step go ahead and punch out every stitching hole before you proceed to cutting the parts on their outlines.

You should now be left with a couple of parts that should go together to form a nice little bag. Here's how:

Use part 3 to fasten the D ring on top of part 2. This part is intentionally less wide so make sure to apply some tension during sewing. You next need to sew part 4 on top of part 2, after passing the D ring through it. This is the front part and we're done with it so let's get to the back.

Part 1 has two split edges that need to be joined using cross stitching starting from the outside of the leather piece and going inwards. Parts 7(the belt loops) need to be joined with part 1 and you're pretty much done with the back too. You may insert the ball head studs before or after you're done, it's up to your personal preference.

The locking strap(part 5) needs to be joined with the smaller part 6, together then being sewn on top of part 1 where the corresponding stitching holes are marked out.

You're now left with stitching the assembled parts together. This is the last thing you need to do and the most time consuming, but you should be done in about half an hour.

I hope you had fun and I'd like to hear from you after your done or if you're having any trouble. Also check out my page <https://leatherhubpatterns.com> from time to time as I will be adding more stuff in the future. Thank you again